Technical Data Sheet | **Manufacturer handbook data**

Revision 01 | 02 November 2026 | English

EVA Solvent-Based Screen Ink

Solvent-based inks

FIELD OF APPLICATION

For screen printing on EVA and relevant sports-goods applications.

CHARACTERISTICS

The source describes a two-component system and adhesion to EVA; do not substitute sole-spray instructions.

MATERIAL AND PROCESS

Process route: Screen printing

Material references: EVA

SELECTION NOTE

Confirm the exact supplied grade, substrate finish and complete system before a production trial. This document translates handbook information; it does not certify performance on every material.

REPORTED PRODUCT DATA

Property	Handbook information
Pack size	4 kg / 16 kg
Stated shelf life	12 months
Adhesion	Cross-cut test mentioned; rating not stated
Alcohol resistance	Anhydrous ethanol, 500 g load, 100 rubs; method not stated
Salt-spray test	5% NaCl, pH 5.5 / 8.0, 48 h; method not stated
Petrol resistance	Petrol exposure for 30 min; method not stated
Thermal cycling	-20 / 80 deg C, 2 h each, 12 cycles; method not stated

Reported values retain source limitations. Test methods, sample preparation and conditions must be confirmed before using a result as a production acceptance criterion.

Revision 01 | 02 November 2026 | English

TYPE OF PACKING

4 kg / 16 kg.

SHELF LIFE AND STORAGE

Stated shelf life: 12 months.

Confirm storage temperature, container conditions and batch dating with the supplier. Shelf life is not the working time after components have been mixed.

APPLICATION REVIEW

Provide the material, intended operation, existing surface treatment and required result when requesting technical advice.

Obtain the current grade-specific instructions for compatible additives, application settings, drying and final conditioning. Carry out a trial on the actual construction before a commercial run.

COLOUR AND FINISH

Where relevant, provide the target colour and finish together with a substrate sample. This sheet does not assign colour codes or availability that are absent from the source.

PRECAUTIONS

1. Use the current exact-grade SDS for handling, storage, transport and disposal. This TDS does not replace the SDS.

2. Follow the SDS and site procedures for protective equipment, ventilation, spills and waste.

3. Confirm product and material compatibility. Do not treat a method-only entry or an unspecified unit as an approved result.

4. Regulatory or restricted-substance conformity requires the relevant report and scope. General handbook wording is not an independent certification.

GRADE CONFIRMATION

The source contains incomplete measurement information or a grade / route detail that requires confirmation. Refer to the qualifiers on page 1 when discussing this product.

TECHNICAL CONTACT

StrideChem
Manufacturing in China
Email: alex@stridechem.in
WhatsApp: +86 177 5965 5021

Contact the technical team

DOCUMENT BASIS

English product information based on the supplied Yunrui manufacturer technical handbook. Technical review copy; unresolved source details have not been invented.

SC-TDS-056 | Revision 01