Technical Data Sheet **Manufacturer handbook data**

Revision 01 | 02 November 2026 | English

YR Clear Anti-Yellowing High-Density Base

High-density & topcoats

FIELD OF APPLICATION

For raised screen printing on footwear, apparel, crafts, bags and packaging applications.

CHARACTERISTICS

The source describes transparency, flexibility, hydrolysis resistance and suitability for manual or automatic high-density printing.

MATERIAL AND PROCESS

Process route: Screen printing / finish

Material references: Textile

SELECTION NOTE

Confirm the exact supplied grade, substrate finish and complete system before a production trial. This document translates handbook information; it does not certify performance on every material.

REPORTED PRODUCT DATA

Property	Handbook information
Pack size	5 kg / 20 kg pail
Stated shelf life	6 months
Viscosity	65,000-75,000; unit, method and temperature not stated
Flex test	More than 120,000 cycles; method not stated
Pull test	5 kg or above; method not stated
Yellowing test	4.5 (grade; standard not stated)
Build rate	Fast (qualitative)
Transparency	Good (qualitative)

Reported values retain source limitations. Test methods, sample preparation and conditions must be confirmed before using a result as a production acceptance criterion.

Technical Data Sheet **Manufacturer handbook data**

Revision 01 | 02 November 2026 | English

TYPE OF PACKING

5 kg / 20 kg pail.

SHELF LIFE AND STORAGE

Stated shelf life: 6 months.

Confirm storage temperature, container conditions and batch dating with the supplier. Shelf life is not the working time after components have been mixed.

APPLICATION REVIEW

Provide the material, intended operation, existing surface treatment and required result when requesting technical advice.

Obtain the current grade-specific instructions for compatible additives, application settings, drying and final conditioning. Carry out a trial on the actual construction before a commercial run.

COLOUR AND FINISH

Where relevant, provide the target colour and finish together with a substrate sample. This sheet does not assign colour codes or availability that are absent from the source.

PRECAUTIONS

1. Use the current exact-grade SDS for handling, storage, transport and disposal. This TDS does not replace the SDS.

2. Follow the SDS and site procedures for protective equipment, ventilation, spills and waste.

3. Confirm product and material compatibility. Do not treat a method-only entry or an unspecified unit as an approved result.

4. Regulatory or restricted-substance conformity requires the relevant report and scope. General handbook wording is not an independent certification.

GRADE CONFIRMATION

The source contains incomplete measurement information or a grade / route detail that requires confirmation. Refer to the qualifiers on page 1 when discussing this product.

TECHNICAL CONTACT

StrideChem
Manufacturing in China
Email: alex@stridechem.in
WhatsApp: +86 177 5965 5021

Contact the technical team

DOCUMENT BASIS

English product information based on the supplied Yunrui manufacturer technical handbook. Technical review copy; unresolved source details have not been invented.

SC-TDS-026 | Revision 01